



WLFW INDUSTRIAL LLC

SKF GE 260 ES-2RS Spherical Plain Bearings - Radial



Bearing No. GE 260 ES-2RS

GE 260 ES-2RS Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Radial
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	57.051
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Not Applicable
Relubricatable	Yes
Enclosure	2 Seals
Other Features	2 Piece Double Lip Seals Lubrication Hole and an Annular Groove in Both Rings
Long Description	260MM Bore; 110MM Housing Width; 370MM Outside Diameter; Spherical Plain; Steel Outer Member; Steel Ball; No Liner; 150MM Overall Width; Relubricatable
Inch - Metric	Metric
Category	Plain Bearings Spherical Radial
UNSPSC	31171515



WLFW INDUSTRIAL LLC

Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	GE 260 ES-2RS
Weight / LBS	113.538
D	14.567 Inch 370 Millimeter
B	5.906 Inch 150 Millimeter
d	10.236 Inch 260 Millimeter
Housing Width	4.331 Inch 110 Millimeter
bore diameter:	260 mm
inner ring material:	Steel
outside diameter:	370 mm
outer ring width:	110 mm
misalignment angle:	7 °
grade:	Commercial/Industrial
inner ring width:	150 mm
radial static load capacity:	15300 kN
bearing type:	Radial
radial dynamic load capacity:	3050 kN
lubrication type:	Requires Lubrication
operating temperature range:	-30 to +130 ° C ° F
closure type:	Sealed
overall width:	150 mm
outer ring material:	Steel
manufacturer upc number:	7316577035547
Lubricant	Regular relubrication – grease
Design (sliding contact surface combination)	Steel/steel



WLFW INDUSTRIAL LLC

Sealing solution	Double-lip seals
d	260 mm
D	370 mm
B	150 mm
C	110 mm
	7 °
d _k	325 mm
b	15.5 mm
b ₁	15.5 mm
M	7 mm
r ₁ min.	1.1 mm
r ₂ min.	1.1 mm
d _a min.	273 mm
d _a max.	288 mm
D _a min.	321.5 mm
D _a max.	359 mm
r _a max.	1 mm
r _b max.	1 mm
Basic dynamic load rating C	3050 kN
Basic static load rating C ₀	15300 kN
Specific dynamic load factor K	100 N/mm ²
Specific static load factor K ₀	500 N/mm ²
Material constant K _M	330
Mass plain bearing	51.5 kg